

3100-BOS-R1 SYSTEM



Phone: 403-529-9645 Fax: 403-527-1369
WWW.CORELUBE.COM

Accommodates Wire Rope Sizes From: .472" (12mm) to 3" (76mm)

The CORELUBE ADVANTAGE FOR THE MINING INDUSTRY

Designed to apply self penetrating Medium & Heavy Oils up to NLGI #0 Soft Grease.

Don't confuse the BOS systems with grease applicators. (There is no comparison)

3100-BOS Collar



Optional Groove Cleaner

Light Weight
Extremely Tough

ADVANTAGES

- High rope speed lubrication.
- Even lubricant coverage.
- No lubricant wastage.
- Eliminates or reduces lubricant fling-off.
- One brush size covers a large range of rope sizes. Eliminates the need for a rubber seal for every size of wire rope.
- Bushings remove exterior contaminants.
- Bushings snap into the collar without tools.
- Cables deformities can be run through the collar.
- Operates at any angle or direction.
- The same pump fits all sizes of containers from a pail to a drum.
- The collar is extremely strong & light weight.
- Easy to use.

3100-BOS-R1 System



(3) Sizes Available



4100-BOS
4.5" Cable

3100-BOS
3" Cable

2100-BOS
1 5/8" Cable



Reduce maintenance time & increase your wire rope life.



Cases Available

3100-BOS-R1 SYSTEM



Phone: 403-529-9645 Fax: 403-527-1369
WWW.CORELUBE.COM

Accommodates Wire Rope Sizes From: .472” (12mm) to 3” (76mm)

The CORELUBE ADVANTAGE FOR THE MINING INDUSTRY
Designed to apply self penetrating Medium & Heavy Oils up to NLGI #0 Soft Grease.




- Accommodates wire ropes from: 12mm to 76mm (0.472” to 3.0”)
- Same pump fits all container sizes.




12 Strand Groove Cleaner




See our Groove Cleaner brochure for more information.



16 Round Strands



6 Round Strands



6 Triangular Strands

Our Groove Cleaners fit all types and sizes of wire ropes from 3 to 18 Outer Strands.

CoreLube
Volume Calculator

ENTER

| | | |
|-------------------|-------|---------------|
| Cable Diameter | 20.8 | mm |
| Cable Length | 5.000 | Meters |
| Number Strands | 6 | Strands |
| Coating Thickness | 0.020 | mm |
| Cable Speed | 1.30 | Meters / Sec. |
| Pump Dial Setting | 220 | |
| Total Volume | 1.8 | Litres |
| | 6.5 | US Gal. |
| Total Run Time | 12.82 | Minutes |
| | 0.21 | Hours |

Click here to go to the calculator

On Line Volume Calculators